

Operating Requirements

Line Voltage: 120V to 240V AC
Frequency: 50Hz to 60Hz
Operating Temperature: -4° to 104° F (-20° to 40° C)
Storage Temperature: -22° to 140° F (-30° to 60° C)
Relative Humidity: 0 to 95% Non-Condensing

Charging

Current: 10 Amps DC
Voltages: 6V, 12V
Chemistry: Lead-Acid and Lithium
Types: Wet, Gel, MF, CA, EFB, AGM, Lithium
Capacity Range: Up to 230 Amp-Hours
Maintenance: All Battery Sizes

Power

Consumption: 150 Watts (Max)
Efficiency: 87% (120VAC / 230VAC)

Protection

IP Rating: IP65

Safety

Short-Circuit: Yes
Open-Circuit: Yes
Overheating: Yes
Overcharge: Yes
Spark-Proof: Yes
Reverse Polarity: Yes

Product Size

Height: 7.1 Inches (180mm)
Width: 3.6 Inches (92mm)
Depth: 2.3 Inches (59mm)
Weight: 3.33 Pounds (1.5kg)

Cord Management

DC Cable + Clamp Length: 77 Inches (195cm)
DC Cable Size: 14 AWG
DC Fuse Size: 20 AMP MINI @ Blade Fuse
AC Cable Length: 71.7 Inches (182cm)
AC Cable Size: 18 AWG
Oil, gas, grease, water, chemical, UV, abrasion resistant

Limited Warranty

3-Year Limited Warranty