

Operating Requirements

Line Voltage: 100V to 240V AC

Frequency: 50Hz to 60Hz

Operating Temperature: -4° to 104° F (-20° to 40° C)

Storage Temperature: -22° to 140° F (-30° to 60° C)

Relative Humidity: 0 to 95% Non-Condensing

Charging

Current: 2 Amps DC

Voltages: 12V DC

Chemistry: Lead-Acid

Types: Wet Cell (Flooded), Gel Cell, Calcium, AGM, Enhanced Flooded Battery or any other Maintenance-Free Battery

Capacity Range: Up to 40 Amp-Hours

Maintenance: All Battery Sizes

Power

Consumption: 28 Watts (Max)

Efficiency: 87%

Protection

IP Rating: IP65

Safety

Short-Circuit: Yes

Open-Circuit: Yes

Overheating: Yes

Overcharge: Yes

Spark-Proof: Yes

Reverse Polarity: Yes

Size and Weight

Height: 1.60 Inches (41 mm)

Width: 3.50 Inches (89 mm)

Depth: 2.34 Inches (59 mm)

Weight: 0.50 Pounds (0.23 kg)

Cord Management

DC Cable Length: 24 Inches (609mm)

DC Cable Size: 18 AWG

DC Fuse Size: 10 Amp MINI ® Blade Fuse

AC Cable Length: 24 Inches (609mm)

AC Cable Size: 18 AWG

Limited Warranty

3-Year Limited Warranty