

Operating Requirements

Line Voltage: 120V to 240V AC

Frequency: 50Hz to 60Hz

Operating Temperature: -4° to 104° F (-20° to 40° C)

Storage Temperature: -22° to 140° F (-30° to 60° C)

Relative Humidity: 0 to 95% Non-Condensing

Charging

Current: 5 Amps DC

Voltages: 6V, 12V

Chemistry: Lead-Acid and Lithium

Types: Wet, Gel, MF, CA, EFB, AGM, Lithium

Capacity Range: Up to 120 Amp-Hours

Maintenance: All Battery Sizes

Power

Consumption: 75 Watts (Max)

Efficiency: 86% (120VAC / 230VAC)

Protection

IP Rating: IP65

Safety

Short-Circuit: Yes

Open-Circuit: Yes

Overheating: Yes

Overcharge: Yes

Spark-Proof: Yes

Reverse Polarity: Yes

Product Size

Height: 4.6 Inches (117mm)

Width: 2.9 Inches (74mm)

Depth: 1.9 Inches (48mm)

Weight: 1.5 Pounds (0.68kg)

Cord Management

DC Cable + Clamp Length: 77 Inches (195cm)

DC Cable Size: 16 AWG

DC Fuse Size: 10 AMP MINI ® Blade Fuse

AC Cable Length: 71.7 Inches (182cm)

AC Cable Size: 18 AWG

Oil, gas, grease, water, chemical, UV, abrasion resistant

Limited Warranty

3-Year Limited Warranty