LiFePO4 BATTERY


PGLM50

12V / 50AH / 640WH

Pro-Guide®


LITHIUM






UNIT SPECIFICATIONS		
Nominal Voltage	12.8V	
Rated Capacity	50Ah	
Circuit Protection	Over Charge, Over Discharge, Over Current Over Temp, Short, Balance	
Cycle Life	3000 times Cycles @100% DOD 6000 times @ 80% DOD	
Monthly Self Discharge	Less Than 2%	
Efficiency of Charge	100% @0.5C	
Efficiency of Discharge	96-99% @1C	
Charge Voltage	14.6±0.2V	
Standard Charge Current	10A	
Max Charge Current	25A	
Standard Discharge Current	10A	
Max Continuous Current	50A	
Discharge Cut-Off Voltage	10V	
Charge Temperature	0˚C to 55˚C	
Discharge Temperature	-20˚C to 60˚C	@60±25% Relative Humidity
Storage Temperature	-20˚C to 45˚C	
Dimensions	197*165*169*mm	
Case/IP Class	Plastic Case/IP65	
Terminal	M6	
Appx Weight	5.3kg/11.68lbs	

DIFFERENT TEMPERATURE DISCHARGE CURVE (.5C)



DIFFERENT DOD DISCHARGE CYCLE LIFE CURVE



Pro-Guide® is a registered trademark of *proguidebatteries.com*

CERTIFICATIONS: IATF16949; ISO9001; IS14001; ISO18001; UN38.3