


VMAX LFP2454MBH Lithium Battery Datasheet

Chemistry	Lithium (LiFePO4)
Group Size	27
Nominal Voltage	25.6 Volts
Capacity (20-hour rate)	54Ah
Energy	1382 Wh
Max. Continuous Discharge Amps	100 Amps
Max. 3-Second Discharge Amps	150 Amps
Charging Voltage	28.8V - 29.2V
Recommended Charging Current	5A - 50A
Max Charging Current	100 Amps
Terminals	M8 x 1.25 Threaded Inserts
Polarity	+ Left / - Right
Length	12.08" (30.7 cm)
Width	6.61" (16.8 cm)
Height	8.35" (21.2 cm)
Weight	27.5 lbs (12.5 kg)
High Voltage Cut-Off	30.0 Volts
Low Voltage Cut-Off	20.0 Volts
Discharge Over-Current Protection	>110A (10s delay), >200A (1s delay)
Charging Over-Current Protection	>110A (10s delay), >200A (1s delay)
Discharge Temp Range	-4°F - 150°F (-20°C - 66°C)
Charging Temp Range	32°F - 113°F (0°C - 45°C)
Storage Temp Range	-4°F-113°F (-20°C - 45°C)
Heater "On" Temp	32°F (0°C)
Cycle Life	100% DOD: ~3000 cycles @ 50A, 77°F
Design Life	~10 Years
Efficiency	>98%
Certifications	IP67, UN 38.3, CE

Information sourced from vmaxtanks.com August 2026 and is subject to change.



GMI ENERGY



We Power Your Life®