

# VMAX V20-600 SLA Battery Datasheet

<b>Type</b>	Deep-Cycle AGM
<b>Voltage</b>	12 Volts
<b>Capacity (20-hour rate)</b>	20Ah
<b>Reserve Capacity</b>	40 Minutes (25A to 10.5V)
<b>Energy</b>	240Wh
<b>Cold Cranking Amps</b>	190 CCA's
<b>Marine Cranking Amps</b>	240 MCA's
<b>Terminals</b>	M6 Inserts
<b>Polarity</b>	- Left / + Right
<b>Length</b>	7.00" (178 mm)
<b>Width</b>	3.00" (76 mm)
<b>Height</b>	6.60" (168 mm)
<b>Weight</b>	13.0 lbs (5.9 kg)
<b>Charging Current</b>	2 - 7 Amps
<b>Charging Voltage</b>	14.4 - 14.9 Volts
<b>Float Voltage</b>	13.5 - 13.8 Volts
<b>Discharge Temp Range</b>	-4°F to 140°F
<b>Charging Temp Range</b>	14°F to 140°F
<b>Storage Temp Range</b>	-4°F to 140°F
<b>Cycle Life</b>	1,600 Cycles at 25% DOD 900 Cycles at 50% DOD 550 Cycles at 80% DOD
<b>Float Service Life</b>	8-10 Years
<b>UPC</b>	760921777930

Information sourced from vmaxtanks.com April 2026 and is subject to change.

