


VMAX XTR27-110 AGM Deep Cycle Battery Datasheet

Type	Dual Purpose AGM (Starting + Deep Cycle)
Group Size	27
Nominal Voltage	12 Volts
Cold Cranking Amps	730 Amps
Marine Cranking Amps	880 Amps
Capacity (20-hour rate)	110Ah
Reserve Capacity	220 minutes (25A to 10.5V)
Energy	1.46 kWh
Terminals	SAE Posts + 5/16" Studs
Polarity	+ Left / - Right
Length	12.0" (305 mm)
Width	6.6" (168 mm)
Height	8.5" (216 mm) / 9.2" (234 mm) w/terminals
Weight	67 lbs (30.4 kg)
Charging Current	10 - 35 Amps
Charging Voltage	14.6V - 14.9V
Float Voltage	13.5V - 13.8V
Discharge Temp Range	-4°F - 140°F
Charging Temp Range	32°F - 120°F
Storage Temp Range	-4°F - 140°F
Float Service Life	10 - 12 Years
Cycle Life	2,600 Cycles at 25% Depth of Discharge (DOD) 1,000 Cycles at 50% DOD 600 Cycles at 80% DOD
Internal Resistance	3.5 mΩ
UPC	030955763576

Information sourced from vmaxtanks.com July 2026 and is subject to change.



GMI ENERGY



We Power Your Life®