


VMAX XTR4D-250 AGM Deep Cycle Battery Datasheet

Type	Dual Purpose AGM (Starting + Deep Cycle)
Group Size	4D
Nominal Voltage	12 Volts
Cold Cranking Amps	1100 Amps
Marine Cranking Amps	1350 Amps
Capacity (20-hour rate)	250Ah
Reserve Capacity	550 minutes (25A to 10.5V)
Energy	3.3 kWh
Terminals	3/8" Studs & SAE Top Posts
Length	20.6" (523 mm)
Width	9.45" (240 mm)
Height	8.6" (218 mm) / 9.4" (239 mm) w/terminals
Weight	143 lbs (64.9 kg)
Charging Current	15 - 70 Amps
Charging Voltage	14.6V - 14.8V
Float Voltage	13.5V - 13.8V
Discharge Temp Range	-4°F - 140°F
Charging Temp Range	0°F - 120°F
Storage Temp Range	-4°F - 140°F
Float Service Life	10 - 12 Years
Cycle Life	2,600 Cycles at 25% Depth of Discharge (DOD) 1,000 Cycles at 50% DOD 600 Cycles at 80% DOD

Information sourced from vmaxtanks.com July 2026 and is subject to change.



GMI ENERGY



We Power Your LiFe®