

# VMAX XTR12-155 AGM Deep Cycle Battery Datasheet

|                         |                                             |
|-------------------------|---------------------------------------------|
| Type                    | Dual Purpose AGM (Starting + Deep Cycle)    |
| Group Size              | 31 (~1 inch taller than standard)           |
| Voltage                 | 12V                                         |
| Capacity (20-hour rate) | 155 Ah                                      |
| Reserve Capacity        | 25A @ 1.75V/Cell: 325 minutes               |
| Cold Cranking Amps      | 850A                                        |
| Marine Cranking Amps    | 1,150A                                      |
| Terminals               | SAE Posts + 5/16" Studs                     |
| Polarity                | + Left / - Right                            |
| Length                  | 12.90" (328 mm)                             |
| Width                   | 6.9" (175 mm)                               |
| Height                  | 10.0" (254 mm) / 10.8" (274 mm) w/terminals |
| Weight                  | 91 lbs                                      |
| Charging Current        | 10 - 40 Amps                                |
| Charging Voltage        | 14.6V - 14.9V                               |
| Float Voltage           | 13.6V - 13.8V                               |
| Discharge Temp Range    | -4°F - 140°F                                |
| Charging Temp Range     | 32°F - 120°F                                |
| Storage Temp Range      | -4°F - 140°F                                |
| Float Service Life      | 10 - 12 Years                               |
| Internal Resistance     | 3.1 mΩ                                      |
| UPC                     | 030955763545                                |

Information sourced from vmaxtanks.com December 2025 and is subject to change.

